



# 210 BALER



**The First High-Capacity, High-Density,  
Commercial Grade Baler.**

---



**210**



## The Marcrest of Balers

Setting the new pace for hay bale production, the Marcrest 210 Baler eliminates the productivity bottleneck of traditional balers and provides the first Bale Baron 5250 integrated windrow-to-bundle system for high-volume small bale production that's ready for market all in one step. With only one operator, a single tractor and the complete Marcrest system, you can now bale and bundle:

**20 TONNES/HR**  
**1000\*** BALES PER HOUR  
**20kg, 6-7 FLAKES**

**17 TONNES/HR**  
**850\*** BALES PER HOUR  
**20kg, 8-9 FLAKES**

**27 TONNES/HR**  
**850\*** BALES PER HOUR  
**32kg, 8 FLAKES**

\*Peak performance shown. Refer to chart on [marcrestmfg.com](http://marcrestmfg.com)

Now with the Marcrest 210 Baler and Bale Baron 5250, hay growers are maximizing operational efficiency by significantly increasing output per person. With premium components and commercial-grade construction, the 210 Baler also raises expectations on equipment durability and ultimately longer life. Find your local Marcrest dealer at [www.marcrestmfg.com](http://www.marcrestmfg.com) for more information on the Marcrest 210 Baler.



# FEATURES



## Variable Speed Camless Pickup

The ground speed matched camless pickup head feeds the double auger and rotor for combined superior feeding efficiency.



## Triple Rasspe Tailless Knotter

The triple tailless knotter is designed to create a stronger knot without the use of a knife arm.



## Pick-up Head Swivel Wheels

Supporting the pick-up head are two swivel wheels with adjustments for consistent minimum ground clearance.



## In-Cab Control Panel

Using the LCD screen display, the in-cab tablet provides fingertip control of all baler functions.



## Auto-Reset Driveline Clutch

Protecting the entire baler from power overload without using shear pins is the auto-reset clutch. Simply slow down RPMs to allow the driveline to re-engage and then continue baling as normal.



## 120 Strokes / Min

Packing in the hay fast and tight is the plunger running at 120 strokes per minute using the momentum of the large diameter 172 kg flywheel.



## 36cm x 46cm Bale Size

Producing bales in the standard 36cm x 46cm size, the 210 uses three strings to create consistent and uniform bales.



## Onboard Hydraulic System

Self contained onboard hydraulic system for efficient and contamination free management of baler's hydraulic functions.



## Pass-Through Hydraulics

The 210 Baler provides hydraulic ports at the rear of the unit to easily connect the Bale Baron 5250 for streamlining initial setup.



## 250 Hour Grease Intervals

Designed with low maintenance requirements in mind, the 210 Baler features premium components made to last with minimal servicing needed.



## Full Access Shields

Top and side shields fully open to easily access all components. The stuffer and rotor also have dedicated clean-out doors.



## 21 Twine Spools

With a holding capacity of 21 twine spools, the 210 matches high-capacity baling with high-volume twine requirements for in-field efficiency.

# 210 BALER



## 210 BALER SPECIFICATIONS

Bale Size	36cm x 46cm
PTO Speed	540 rpm
Flywheel	172 kgs
Camless Pickup	Standard
Pickup Width	2.5 Meters
Pickup Drive	Variable speed onboard hydraulic
Pickup Tine Bars	5
Pickup Windguard	Spring adjustable swath roller with tines
Pickup Gauge Wheels	16/6.5 - 8 Foam filled swivelling
Auger Protection	Ratcheting torque limiter
Auger Drive	#60 Chain
Rotor Protection	Auto-reset torque limiter
Rotor Drive	Gearbox
Stuffer	3 Tine crank type
Stuffer Drive	Gearbox
Stuffer Protection	Shearbolt

Plunger Speed (540)	120 Strokes/min
Plunger Protection	Auto-reset torque limiter
Knotters	3 Rassepe Tailless
Knotted Protection	Shearbolt
Knotted Fan	Auto-reversing hydraulic
Twine Storage	21 Balls
Chamber Tension	3-Way onboard hydraulic
Tires	500/50/17
Suspension	Standard rubber block
Onboard Hydraulic System	Standard (Pickup drive, bale tension, knotted fan)
Baler Weight (approx)	4.99 Tonnes
Hitch Weight (approx)	.77 Tonnes
Minimum HP Requirement	125 hp (165 hp for baler and 5250 Bale Baron)
Minimum Tractor Weight	Tractor including drawbar weight must be greater than loaded axle weights of towed implements
Tractor Hydraulics	1 Single acting (for pickup lift)



Phone: 1-519-887-9910 Fax: 1-519-291-9914  
 info@marcrestmfg.com marcrestmfg.com

45415 Perth Line 86, Listowel, Ontario, Canada, N4W 3G6

Authorized Dealer